



GH Berlin Windward  
866-946-3927  
www.ghberlinwindward.com

Heading Oil 150

SDS Revision Date: 05/28/2015

## Safety Data Sheet

### 1. Identification

#### 1.1. Product identifier

<b>Product Identity</b>	Heading Oil 150
<b>Alternate Names</b>	Heading Oil 150

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

<b>Intended use</b>	Lubricating Oil
<b>Application Method</b>	See Technical Data Sheet.

#### 1.3. Details of the supplier of the safety data sheet

<b>Company Name</b>	Northeast Products Company 52 Ferry Street Fall River, MA, 02722
---------------------	--

#### Emergency

<b>24 hour Emergency Telephone No.</b>	1-800-225-8150
<b>Customer Service: Northeast Products Company</b>	1-800-225-8150

### 2. Hazard(s) identification

#### 2.1. Classification of the substance or mixture

No applicable GHS categories.

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.

No applicable GHS categories.

#### **[Prevention]:**

No GHS prevention statements

#### **[Response]:**

No GHS response statements

#### **[Storage]:**

No GHS storage statements



GH Berlin Windward  
866-946-3927  
www.ghberlinwindward.com

## Heading Oil 150

SDS Revision Date: 05/28/2015

### Safety Data Sheet

[Disposal]:

No GHS disposal statements

## 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Lubricating Oils, petroleum, hydrotreated-spent CAS Number: 0064742-58-1	50 - 85	Not Classified	[1]
Calcium Sulfonate CAS Number: N/A	1.0-10	Not Classified	[1]
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil-unspecified CAS Number: 0064742-70-7	1.0 - 10	Not Classified	[1]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

## 4. First aid measures

### 4.1. Description of first aid measures

<b>General</b>	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
<b>Inhalation</b>	Remove exposed person to fresh air if adverse effects are observed. If breathing is labored, administer oxygen. If breathing has stopped, apply artificial respiration. If irritation persists get medical attention.
<b>Eyes</b>	Flush immediately with water for at least 15 minutes.
<b>Skin</b>	Wash with soap and water. Remove contaminated clothing. Get medical attention if irritation develops. Launder contaminated clothing before re-use and discard shoes and other leather articles saturated with the material.
<b>Ingestion</b>	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.



GH Berlin Windward  
866-946-3927  
www.ghberlinwindward.com

## Heading Oil 150

SDS Revision Date: 05/28/2015

## Safety Data Sheet

### 4.2. Most important symptoms and effects, both acute and delayed

#### Overview

Eyes: May cause eye irritation.  
Skin Absorption: No acute effects expected.  
Skin Contact: May cause skin irritation.  
Inhalation: May Cause respiratory irritation.  
Ingestion: LD 50 not established. Do not ingest.

May cause skin irritation. Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying, defatting, and cracking of the skin.

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

#### Chronic effects

Note to physician. Treat symptomatically

## 5. Fire-fighting measures

### 5.1. Extinguishing media

CO<sub>2</sub>, dry chemical, or foam.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Smoke, Carbon monoxide and other products of incomplete combustion.

### 5.3. Advice for fire-fighters

Recommend wearing self contained breathing apparatus.

ERG Guide No. ----



GH Berlin Windward  
866-946-3927  
www.ghberlinwindward.com

## Heading Oil 150

SDS Revision Date: 05/28/2015

## Safety Data Sheet

### 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

#### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

#### 6.3. Methods and material for containment and cleaning up

Prevent entry into sewers and waterways. Pickup free liquid for recycling/disposal. Absorb small amounts on inert material for disposal.

### 7. Handling and storage

#### 7.1. Precautions for safe handling

None noted

#### 7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Store inside building, away from potential sources of ignition.

Incompatible materials: Strong oxidizing agents and acids.

Keep away from potential sources of ignition. Keep containers closed when not in use. Avoid breathing vapors.

Containers retain material residue. Do not cut, weld, braze, solder, drill, grind or expose containers to heat, flame, spark, or other sources of ignition.

See section 2 for further details. - [Storage]:

#### 7.3. Specific end use(s)

No data available.

### 8. Exposure controls and personal protection

#### 8.1. Control parameters

##### Exposure

CAS No.	Ingredient	Source	Value
0064742-70-7	Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil-unspecified	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit



GH Berlin Windward  
866-946-3927  
www.ghberlinwindward.com

## Heading Oil 150

SDS Revision Date: 05/28/2015

### Safety Data Sheet

N/A	Calcium Sulfonate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0064742-58-1	Lubricating Oils, petroleum, hydrotreated-spent	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m<sup>3</sup> OSHA PEL and 10 mg/m<sup>3</sup> ACGIH.

### Carcinogen Data

CAS No.	Ingredient	Source	Value
0064742-70-7	Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil-unspecified	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
N/A	Calcium Sulfonate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: Yes
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-58-1	Lubricating Oils, petroleum, hydrotreated-spent	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

#### 8.2. Exposure controls

##### Respiratory

Use NIOSH/MSHA approved full face respirator with an organic vapor cartridge if the recommended exposure limit is exceeded. Use self contained breathing apparatus for entry into confined space, or for other poorly ventilated areas.

##### Eyes

Chemical Goggles or faceshield.

##### Skin

Long sleeve shirt recommended. Do not wear rings, watches, or similar apparel that could entrap the material and cause a mild skin reaction. Neoprene, Nitrile, or Viton. or exhaust may be required to maintain air concentrations below recommended exposure limits.

##### Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

##### Other Work Practices

Use local exhaust ventilation to control mists or vapors. Additional ventilation



GH Berlin Windward  
866-946-3927  
www.ghberlinwindward.com

## Heading Oil 150

SDS Revision Date: 05/28/2015

## Safety Data Sheet

may be required to maintain air concentrations below recommended exposure limits. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

### 9. Physical and chemical properties

Appearance	Amber Liquid
Odor	petroleum odor
Odor threshold	Not determined
pH	Not Measured
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	Not Measured
Flash Point	380°F (COC)
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	<b>Lower Explosive Limit:</b> Not Measured <b>Upper Explosive Limit:</b> Not Measured
Vapor pressure (Pa)	Not Measured
Vapor Density	Not Measured
Specific Gravity	0.879
Solubility in Water	Insoluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	53-69 cSt @ 40°C Typical

#### 9.2. Other information

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

### 10. Stability and reactivity

#### 10.1. Reactivity

Hazardous Polymerization will not occur.

#### 10.2. Chemical stability

Material is stable.

#### 10.3. Possibility of hazardous reactions



GH Berlin Windward  
866-946-3927  
www.ghberlinwindward.com

## Heading Oil 150

SDS Revision Date: 05/28/2015

### Safety Data Sheet

No data available.

#### 10.4. Conditions to avoid

Excessive heat and open flame.

#### 10.5. Incompatible materials

Strong oxidizing agents and acids.

#### 10.6. Hazardous decomposition products

Smoke, Carbon monoxide and other products of incomplete combustion.

## 11. Toxicological information

### Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Lubricating Oils, petroleum, hydrotreated-spent CAS Number: 0064742-58-1	> 5,000.00, Rat - Category: NA	No data available	No data available	5.70, Rat - Category: NA	No data available
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil-unspecified - (64742-70-7)	No data available	No data available	No data available	No data available	No data available
Calcium Sulfonate	No data available	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable



GH Berlin Windward  
866-946-3927  
www.ghberlinwindward.com

## Heading Oil 150

SDS Revision Date: 05/28/2015

### Safety Data Sheet

Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

## 12. Ecological information

### 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Lubricating Oils, petroleum, hydrotreated-spent CAS Number: 0064742-58-1	5,000.00, Oncorhynchus mykiss	1,000.00, Daphnia magna	Not Available
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil-unspecified - (64742-70-7)	Not Available	Not Available	Not Available
Calcium Sulfonate	100-1000	Not Available	100-1000

### 12.2. Persistence and degradability

There is no data available on the preparation itself.

### 12.3. Bioaccumulative potential

Not Measured

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

### 12.6. Other adverse effects

No data available.

## 13. Disposal considerations

### 13.1. Waste treatment methods





GH Berlin Windward  
866-946-3927  
www.ghberlinwindward.com

## Heading Oil 150

SDS Revision Date: 05/28/2015

### Safety Data Sheet

Waste management should be in compliance with federal, state, and local laws.

#### 14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: No		
14.6. Special precautions for user	No further information		

#### 15. Regulatory information

<b>Regulatory Overview</b>	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
<b>Toxic Substance Control Act ( TSCA)</b>	All components of this material are either listed or exempt from listing on the TSCA Inventory.
<b>WHMIS Classification</b>	Not Regulated

<b>US EPA Tier II Hazards</b>	<b>Fire:</b> No
	<b>Sudden Release of Pressure:</b> No
	<b>Reactive:</b> No
	<b>Immediate (Acute):</b> No
	<b>Delayed (Chronic):</b> No

#### EPCRA 311/312 Chemicals and RQs:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### EPCRA 313 Toxic Chemicals:



GH Berlin Windward  
866-946-3927  
www.ghberlinwindward.com

## Heading Oil 150

SDS Revision Date: 05/28/2015

### Safety Data Sheet

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Carcinogens (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Developmental Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Female Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Male Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**New Jersey RTK Substances (>1%) :**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Pennsylvania RTK Substances (>1%):**

Oils, lard

## 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

**This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.**

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of the Northeast Products Company's knowledge; however, Northeast Products Company makes no warranty whatsoever, expressed or implied, of MERCHANT ABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, regarding the accuracy of such data or the results to be obtained from the use thereof. The Northeast Products Company assumes no responsibility for injury to recipient or to third persons or for any damage to any property and recipient assumes all such risks.

End of Document