

1. Chemical Product and Company Identification

Navi-Guard Keldri #6



G.H. Berlin Lubricants • Windward Petroleum, Inc.

800-426-7754 • 866-946-3927

www.ghberlin.com • www.windwardpetroleum.com

CAS Registry Number:	Not Applicable for mixtures
Chemical Name:	Petroleum Hydrocarbon plus Additives
Preparation/Revision Data:	November 2012
Emergency Phone Number:	800-225-8150

2. Composition/Information on Ingredients

Mineral Spirits (mixed distillate)	85-90%	CAS 64742-47-8
Corrosion Preventive Additives	Proprietary	Proprietary
WHMIS Classification		B3

3. Hazardous Identification

Principle Hazards:	Eyes:	May cause eye irritation
	Skin Absorption:	No acute effects expected
	Skin Contact:	May cause skin irritation
	Inhalation:	May cause respiratory irritation
	Ingestion:	LD 50 not established. Do not ingest

4. First Aid Measures

Oral:	Do not induce vomiting.
Eye:	Flush immediately with water for at least 15 minutes.
Skin:	Wash with soap and water. Remove contaminated clothing. Get medical attention if irritation develops. Launder contaminated clothing before re-use and discard shoes and other leather articles saturated with the material.
Inhalation:	Remove exposed person to fresh air if adverse effects are observed. If breathing is labored, administer oxygen. If breathing has stopped, apply artificial respiration. If irritation persists, get medical attention.
Additional:	Note to Physician. Treat symptomatically.

5. Fire Fighting Measures

Flash Point (Typical):	141°F min
Upper Flammable Limit:	Not determined
Lower Flammable Limit:	Not determined
Extinguishing Media:	CO ₂ , dry alcohol like foam, dry chemicals.
Special Fire Fighting Procedures:	Recommended wearing self contained breathing apparatus.
Unusual Fire & Explosion Hazards:	None
Auto ignition Temperature:	Not determined
Explosion Data:	Material does not have explosion properties.

6. Accidental Release Measures

Spill procedures:	Prevent entry into sewers and waterways. Pickup free liquid for recycling/disposal. Absorb small amounts on inert material for disposal.
Disposal:	Dispose of in accordance with federal, state, and local laws.

7. Handling and Storage

Handling Procedures:	Keep away from potential sources of ignition. Keep containers closed when not in use. Avoid breathing vapors. Containers retain material residue. Do not cut, weld, braze, solder, drill, grind or expose containers to heat, flame, spark, or other sources of ignition.
Storage Procedure:	Store inside building, away from potential sources of ignition.

8. Exposure control/Personal Protection

Ventilation Procedures:	Use local exhaust ventilation to control mists or vapors. Additional ventilation may be required to maintain air concentrations below recommended exposure limits.
Glove Protection:	Neoprene, Nitrile, or Viton.
Eye Protection:	Chemical goggles or faceshield
Respiratory Protection:	Use NIOSH/MSHA approved full face respirator with an organic vapor cartridge, if the recommended exposure limit is exceeded. Use self contained breathing apparatus for entry into confined space, or for other poorly ventilated areas.
Clothing:	Long sleeve shirt recommended. Do not wear rings, watches or similar apparel that could entrap the material and cause a mild skin reaction.

9. Physical and Chemical Properties

Vapor Pressure:	0.32mm Hg @ 100°F
PH:	Not determined
Specific Gravity:	0.80
Water Solubility:	Insoluble
Odor:	Solvent Odor
Appearance:	Clear Amber liquid
Boiling Point:	325°F
Freezing Point:	Not determined

10. Stability and Reactivity

Stability:	Material is stable
Polymerization:	Will not occur
Chemical Incompatibilities:	Incompatible with acids and strong oxidizers. Avoid heat or open flame.
Thermal Decomposition:	Carbon monoxide and unidentified organic compounds may be formed during combustion.

11. Toxicological Information

Oral Toxicity:	N/A
Eye Irritation:	May cause mild eye irritation
Skin Irritation:	May cause skin irritation. Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying, defatting, and cracking of the skin.
Respiratory Irritation:	N/A

12. Ecological Information

Acute Toxicity:

Fish:	Low toxicity: LC/EC/IC50 > 1000 mg/l
Aquatic Invertebrates:	Low toxicity: LC/EC/IC50 > 1000 mg/l
Algae:	Low toxicity: LC/EC/IC50 > 1000 mg/l

Mobility: Floats on water. Absorbs to soil and has low mobility

Persistence/Degradability: Expected to be readily biodegradable. Oxidizes rapidly by photo-chemical reactions in air.

13. Disposal Considerations

Waste Disposal:	Waste management should be in compliance with federal, state and local laws.
-----------------	--

14. Transport Data

DOT Classification:	Not regulated
Identification:	Combustible Liquid

15. Regulatory Information

US TSCA Inventory:	All components of this material are on the US TSCA inventory
Other TSCA Reg:	None Known
SARA Extremely Hazardous Substance:	This product does not contain greater than 1% of any chemical substance on the SARA Extremely Hazardous Substance list.

16. Other Information

Health-1 Fire-2 Reactivity-0

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of G.H. Berlin Lubricants & Windward Petroleum, Inc.'s knowledge; however, G.H. Berlin Lubricants & Windward Petroleum, Inc. make no warranty whatsoever, expressed or implied, of MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, regarding the accuracy of such data of the results to be obtained from thereof. G.H. Berlin Lubricants & Windward Petroleum, Inc. assume no responsibility for injury to recipient or to third persons or for any damage to any property and recipient assumes all such risks.