



GH Berlin Windward  
866-946-3927  
www.ghberlinwindward.com

KOOL LUBE III

## SAFETY DATA SHEET

10/08/15

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Kool Lube III

**Product Code:** 443630

**Chemical Family:** Lubricant

**Manufacturer:** Northeast Products Co Inc.

52 Ferry St  
Fall River, MA 02721

**Emergency Telephone Number:** 800-225-8150

8am-4pm M-F

## 2. HAZARD IDENTIFICATION

**Hazard statements : DANGER** H304: May be fatal if swallowed and enters airways -  
If swallowed, Immediately call a POISON CENTER.

**WARNING** H315: Causes skin irritation.  
If on skin, wash with plenty of soap and water.



## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Percent	Component	Synonym	CAS#
30-70	Distillates, petroleum, hydrotreated light	Aliphatic Solvent	64742-47-8
30-70	Distillates (petroleum), hydrotreated heavy naphthenic		64742-52-5
0-20	Oils,Lard		8016-28-2

## 4. FIRST AID MEASURES

**EYE:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**SKIN CONTACT:** Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. When symptoms persist or in all cases of doubt seek medical advice. Wash contaminated clothing before re-use.

**INGESTION:** If swallowed, call a poison control centre or doctor immediately. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.



GH Berlin Windward  
866-946-3927  
www.ghberlinwindward.com

KOOL LUBE III

## SAFETY DATA SHEET

10/08/15

**INHALATION:** Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. In case of shortness of breath, give oxygen. Call a physician immediately.

### 5. FIRE FIGHTING MEASURES

**FLASH POINT:** 100°C - Average

**CONDITIONS OF FLAMMABILITY:** NFPA Class IIIA combustible liquid

**FLAMMABLE LIMITS IN AIR:** N/A

**AUTO-IGNITION TEMP:** N/A

**EXTINGUISHING MEDIA:** Water spray or fog, foam, dry chemical, CO<sub>2</sub>

**FIRE FIGHTING INSTRUCTIONS:** Keep storage containers cool with water spray. A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

**FIRE AND EXPLOSION HAZARDS:** Heated containers may rupture. "Empty" containers may retain residue and can be dangerous. Product is not sensitive to mechanical impact or static discharge.

### 6. ACCIDENTAL RELEASE MEASURES

**SPILLS OR LEAKS:** Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations.

### 7. HANDLING AND STORAGE

**HANDLING:** Keep away from sparks or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools. When transferring product, ensure all equipment is electrically grounded before beginning transfer operations. When aerosolizing, misting, or heating this product, do not breathe vapor or mist. Use in a well-ventilated area. Avoid contact with eyes, skin, clothing and shoes.

**SHIPPING/STORING:** Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain residue and can be dangerous.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**EXPOSURE GUIDELINES:**

**COMPONENT EXPOSURE LIMITS**

Contains mineral oil. The exposure limits for oil mist are 5 mg/m<sup>3</sup> OSHA PEL and 10 mg/m<sup>3</sup> ACGIH.

**ENGINEERING CONTROLS:** Avoid creating mist or spray. Avoid splashing. Provide general ventilation to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation or other engineering controls to control airborne levels below applicable exposure limits.

**PERSONAL PROTECTIVE EQUIPMENT —**

**EYE:** Chemical goggles or safety glasses. In case of splashing or aerosol production: protective goggles.



GH Berlin Windward  
866-946-3927  
www.ghberlinwindward.com

KOOL LUBE III

## SAFETY DATA SHEET

10/08/15

**SKIN:** Protective gloves recommended when prolonged skin contact cannot be avoided. Use of natural rubber or equivalent gloves is not recommended. When product is heated and skin contact is likely, wear heat-insulating gloves, boots, and other protective clothing. To avoid prolonged or repeated contact where spills and splashes are likely wear appropriate chemical-resistant face shield, boots, apron, coveralls, long sleeve shirts, or other protective clothing.

**RESPIRATOR:** No respiratory protection is normally required. Use NIOSH-certified P- or R- series particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. Protection provided by air purifying respirators is limited. Do not use N-rated respirators. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

**PERSONAL HYGIENE:** Use good personal hygiene. Wash thoroughly with soap and water after handling product and before eating, drinking, or using tobacco products. Clean affected clothing, shoes, and protective equipment before reuse. Discard leather articles, such as shoes, saturated with these products.

**OTHER:** Where spills and splashes are likely, facilities storing or using these products should be equipped with emergency eyewash and shower, both equipped with clean water, in the immediate work area.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<p><b>Color:</b> Clear  <b>Physical State:</b> Liquid  <b>Odor:</b> Hydrocarbon-like  <b>Vapor Pressure:</b> N/A  <b>Vapor Density:</b> 5.4  <b>Viscosity:</b> Not measured  <b>Spec. Gravity:</b> N/A  <b>Density:</b> 6.7 lb/gal @ 15.5°C- Typical  <b>Solubility:</b> Negligible</p>	<p><b>Boiling Point:</b> 192 - 211 °C  <b>Melting Point:</b> N/A  <b>Freezing Point:</b> N/A  <b>Flash Point:</b> 100°C- Average  <b>Flammability:</b>            Upper explosion limit: Not Measured            Lower explosion limit: Not Measured  <b>Auto Ignition:</b> Not measured  <b>Decomposition temperature:</b> N/A  <b>Octanol/Water Partition Coefficient:</b> N/A</p>
---	--

## 10. STABILITY AND REACTIVITY

**STABILITY:** Stable under normal temperatures and pressures.

**INCOMPATIBLE MATERIALS:** Oxidizing agents

**REACTIVITY:** Stable at normal ambient temperature and pressure.

**HAZARDOUS DECOMPOSITION:** Hazardous gases and vapors produced in fire are oxides of carbon.

## 11. TOXICOLOGICAL INFORMATION



GH Berlin Windward  
866-946-3927  
www.ghberlinwindward.com

KOOL LUBE III

## SAFETY DATA SHEET

10/08/15

**ACUTE EFFECTS:** May be fatal if swallowed. Causes skin irritation.

**REPEATED DOSE EFFECTS:** No information available.

**SENSITIZATION:** Based on best current information, there is no known human sensitization associated with this product.

**MUTAGENICITY:** Based on best current information, there is no known mutagenicity associated with this product.

**CARCINOGENICITY :** Contains no ingredient listed as a carcinogen

**REPRODUCTIVE TOXICITY :** No information available.

**TERATOGENICITY:** No information available.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Distillates, petroleum, hydrotreated light (64742-52-2)	> 5,000.00, Rat - Category: NA	No data available	No data available	No data available	No data available
Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil-unspecified - (64742-52-5)	> 5,000.00, Rat - Category: NA	No data available	No data available	5.70, Rat - Category: NA	No data available
Oils, Lard (8016-28-2)	No data Available	No data available	No data available	No data available	No data available

## 12. ECOLOGICAL INFORMATION

## ECOTOXICITY :

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Distillates, petroleum, hydrotreated light	54.00, Jordanella floridae	68.00, Daphnia magna	Not Available
Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil-unspecified - (64742-52-5)	5,000.00, Oncorhynchus mykiss	1,000.00, Daphnia magna	1,000.00 (96 hr), Scenedesmus subspicatus
Oils, Lard	Not Available	Not Available	Not Available

**PERSISTENCE/DEGRADABILITY :** Readily biodegradable.

**BIOACCUMULATIVE POTENTIAL :** No information available for this product.

**MOBILITY IN ENVIRONMENT :** Base oil component(s) – Low solubility and floats; expected to migrate from water to land.

**OTHER ADVERSE EFFECTS:** N/A

**OCTANOL/WATER PARTITION COEFFICIENT:** N/A

**AQUATIC RELEASE :** Not toxic to aquatic organisms up to water solubility.



GH Berlin Windward  
866-946-3927  
www.ghberlinwindward.com

KOOL LUBE III

## SAFETY DATA SHEET

10/08/15

### 13. DISPOSAL INFORMATION

**DISPOSAL:** Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste.

**USEPA WASTE CODES:** Any unused product or empty containers may be disposed of as non-hazardous in accordance with state and federal requirements. Re-evaluation of the product may be required by the user at the time of disposal, since the product uses, transformations, mixtures, contamination, and spillage may change the classification. If the resulting material is determined to be hazardous, please dispose in accordance with state and federal (40 CFR 262) hazardous waste regulations.

**EMPTY CONTAINERS:** Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, triple-rinsed, properly bunged and promptly returned to a drum reconditioner, or properly disposed.

### 14. TRANSPORTATION INFORMATION

**DOT :** Not regulated. Product does not sustain combustion (49 CFR 173.120(b)(3)).

**PROPER SHIPPING NAME :** Not Regulated

**HAZARD CLASS:** Not regulated

**ID NUMBER:** Not regulated

**LABEL REQUIRED:** Not regulated

**EMERGENCY RESPONSE:** N/A Reference North American Emergency Response Guidebook.

### 15. REGULATORY INFORMATION

**OSHA HAZARDS (HCS 1994):** Aspiration hazard, Moderate skin irritant, Moderate eye irritant.

**TSCA:** All components of this product are listed in **Section 3** are exempted from the TSCA requirements.

**SARA SECTIONS 302 304:** Based on the ingredients listed in **Section 3**, this product does not contain any "extremely hazardous substances" listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

**SARA SECTIONS 311 AND 312 REPORTING:** This product poses the following health hazard(s) as defined in 40 CFR Part 370 and is subject to the requirements of Sections 311 and 312 of Title III of Superfund Amendments and Reauthorization Act of 1986 (SAEA):

Immediate (Acute) Health Hazard:	YES
Delayed (Chronic) Health Hazard:	No
Physical Fire:	No
Physical Sudden Release of Pressure:	No
Physical Reactive:	No



GH Berlin Windward  
866-946-3927  
www.ghberlinwindward.com

KOOL LUBE III

**SAFETY DATA SHEET**

10/08/15

**CERCLA:** Based on the ingredients listed in **Section 3**, this product does not contain any “hazardous substances” listed pursuant to the comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4.

**16. OTHER INFORMATION**

**NFPA RATINGS:** Health: 2 Flammability: 1 Reactivity: 0

**HMIS RATINGS:** Health: 2 Flammability: 1 Reactivity: 0  
(0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme, PPE:- Personal Protection Equipment Index recommendation, \*- Chronic Effect Indicator).

**DATE ISSUED: October 8th, 2015**

**REVISION NO. New SDS**

**REVISION INFORMATION: Not applicable**

**NORTHEAST PRODUCTS CO INC  
52 FERRY STREET  
FALL RIVER, MA 02721  
800-225-8150**

The information on this form is furnished solely for the purpose of compliance with the OSHA Act, and shall not be used for any other purpose. The information herein is given in good faith and is based on data considered accurate. However, no warranty, expressed or implied, is made regarding the accuracy of this data or the results to be obtained from the use thereof. This safety data sheet was prepared for and is to be used only for this product. If the product is used as a component in another product, this safety sheet information may not be applicable.