



GH Berlin Windward
866-946-3927
www.ghberlinwindward.com

SAFETY DATA SHEET

1. Product and Company Identification

Product identifier	Form Oil
Other means of identification	Not available
Recommended use	Release agent
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer:	
Company name	Irving Blending & Packaging
Address	PO Box 1169 Saint John, NB E2L 4E6 Canada
Telephone	1.800.574.5823
E-mail	MSDS@irvingblend.com
Emergency phone number	1.506.648.3060

2. Hazards Identification

Physical hazards	Flammable liquids	Category 4
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2B
	Carcinogenicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 1
	Aspiration hazard	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger
Hazard statement	Combustible liquid. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes skin irritation. Causes eye irritation. Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Avoid breathing mist or vapor. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash thoroughly after handling. Do not eat, drink or smoke when using this product.
Response	In case of fire: Use appropriate media to extinguish. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

If on skin: Wash with plenty of water. Specific treatment (see this label). If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

If exposed or concerned: Get medical advice/attention.

Storage	Store in a well-ventilated place. Keep cool. Store locked up. Keep container tightly closed.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	25% of the mixture consists of component(s) of unknown acute oral toxicity. 25% of the mixture consists of component(s) of unknown acute inhalation toxicity.

3. Composition/Information on Ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Stoddard solvent		8052-41-3	30-60
Distillates (petroleum), light hydrotreated		64742-47-8	10-30
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy		64742-70-7	10-30
Benzene, 1,2,4-trimethyl-		95-63-6	1-5
Nonane		111-84-2	1-5
Benzene, ethyl-		100-41-4	0.1-1
Naphthalene		91-20-3	0.1-1

4. First Aid Measures

Inhalation	If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.
Skin contact	If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Specific treatment (see product label). Take off contaminated clothing and wash it before reuse.
Eye contact	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.
Most important symptoms/effects, acute and delayed	Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention.

5. Fire Fighting Measures

Suitable extinguishing media	Foam. Dry chemical powder.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Combustible liquid.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	--

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop the flow of material, if this is without risk.

Large Spills: Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Use water spray to reduce vapors or divert vapor cloud drift. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage**Precautions for safe handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Do not breathe mist or vapor. Avoid contact with eyes, skin and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Use personal protective equipment as required. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in a cool, dry place out of direct sunlight. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure Controls/Personal Protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
Benzene, ethyl- (CAS 100-41-4)	PEL	435 mg/m3	
		100 ppm	
Naphthalene (CAS 91-20-3)	PEL	50 mg/m3	
		10 ppm	
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	PEL	5 mg/m3	Mist.
Stoddard solvent (CAS 8052-41-3)	PEL	2900 mg/m3	
		500 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value
Benzene, 1,2,4-trimethyl- (CAS 95-63-6)	TWA	25 ppm
Benzene, ethyl- (CAS 100-41-4)	TWA	20 ppm
Naphthalene (CAS 91-20-3)	STEL	15 ppm
	TWA	10 ppm
Nonane (CAS 111-84-2)	TWA	200 ppm
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Benzene, 1,2,4-trimethyl- (CAS 95-63-6)	TWA	125 mg/m3	
		25 ppm	
Benzene, ethyl- (CAS 100-41-4)	STEL	545 mg/m3	
		125 ppm	
		435 mg/m3	
	TWA	100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	100 mg/m3	
Naphthalene (CAS 91-20-3)	STEL	75 mg/m3 15 ppm	
	TWA	50 mg/m3 10 ppm	
Nonane (CAS 111-84-2)	TWA	1050 mg/m3 200 ppm	
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Stoddard solvent (CAS 8052-41-3)	Ceiling	1800 mg/m3	
	TWA	350 mg/m3	

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Benzene, ethyl- (CAS 100-41-4)	0.7 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US ACGIH Threshold Limit Values: Skin designation**

Naphthalene (CAS 91-20-3)

Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles).

Skin protection**Hand protection**

Wear protective gloves.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Wear positive pressure self-contained breathing apparatus (SCBA).

Thermal hazards

Not applicable.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and Chemical Properties

Appearance	Liquid
Physical state	Liquid.
Form	Liquid.
Color	Amber
Odor	Mild petroleum
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	390.2 °F (199 °C)

Pour point	Not available.
Specific gravity	0.82 @ 15°C
Partition coefficient (n-octanol/water)	Not available.
Flash point	158.0 °F (70.0 °C) Cleveland Open Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	Negligible
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	2.6 cSt @ 40°C

10. Stability and Reactivity

Reactivity	Strong oxidizing agents.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

11. Toxicological Information

Information on likely routes of exposure

Ingestion	May be fatal if swallowed and enters airways.
Inhalation	May be fatal if swallowed and enters airways. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful. May cause damage to organs by inhalation.
Skin contact	Causes skin irritation.
Eye contact	Causes eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects.

Components	Species	Test Results
Benzene, 1,2,4-trimethyl- (CAS 95-63-6)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 3160 mg/kg
	Rat	>= 3160 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 2000 ppm, 48 Hours
		3661 ppm

Components	Species	Test Results
<i>Oral</i> LD50	Rat	3280 mg/kg
Benzene, ethyl- (CAS 100-41-4)		
Acute <i>Dermal</i> LD50	Rabbit	15380 mg/kg
<i>Inhalation</i> LC50	Rat	4000 ppm, 4 Hours
<i>Oral</i> LD50	Rat	5460 mg/kg
		3500 mg/kg
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)		
Acute <i>Dermal</i> LD50	Rabbit	> 2000 mg/kg
<i>Inhalation</i> LC50	Rat	> 2.8 mg/l/4h
<i>Oral</i> LD50	Rat	> 5000 mg/kg
Naphthalene (CAS 91-20-3)		
Acute <i>Dermal</i> LD50	Rabbit	> 2000 mg/kg
		> 20 g/kg
		> 2 g/kg
	Rat	2500 mg/kg
<i>Inhalation</i> LC50	Rat	> 340 mg/m3, 1 Hours
		> 0.2 mg/l, 4 Hours, (Vapor)
		> 0.1 mg/l, 4 Hours, (Dust)
		500 mg/m3, 8 Hours
		141 ppm, 4 Hours
		85 mg/m3, 4 Hours, (dust)
<i>Oral</i> LD50	Guinea pig	1200 mg/kg
	Mouse	533 mg/kg
	Rat	490 mg/kg
Nonane (CAS 111-84-2)		
Acute <i>Inhalation</i> LC50	Rat	3200 ppm, 4 Hours
<i>Oral</i> LD50	Rat	>= 15000 mg/kg
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)		
Acute <i>Inhalation</i> LC50	Not available	
<i>Oral</i> LD50	Not available	

Components	Species	Test Results
Stoddard solvent (CAS 8052-41-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 3000 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 5500 mg/m3
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Causes eye irritation.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Respiratory sensitization	Not available.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer. Contains < 3% (w/w) DMSO-extract	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Benzene, ethyl- (CAS 100-41-4)	2B Possibly carcinogenic to humans.	
Naphthalene (CAS 91-20-3)	2B Possibly carcinogenic to humans.	
Stoddard solvent (CAS 8052-41-3)	3 Not classifiable as to carcinogenicity to humans.	
US. National Toxicology Program (NTP) Report on Carcinogens		
Naphthalene (CAS 91-20-3)	Reasonably Anticipated to be a Human Carcinogen.	
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Narcotic effects.	
Specific target organ toxicity - repeated exposure	Causes damage to organs through prolonged or repeated exposure.	
Aspiration hazard	May be fatal if swallowed and enters airways.	
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. Causes damage to organs through prolonged or repeated exposure.	
Further information	Not available.	

12. Ecological Information

Ecotoxicity	See below		
Components		Species	Test Results
Benzene, 1,2,4-trimethyl- (CAS 95-63-6)			
Crustacea	EC50	Daphnia	6.14 mg/L, 48 Hours
Aquatic			
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>)	7.19 - 8.28 mg/l, 96 hours
Benzene, ethyl- (CAS 100-41-4)			
Algae	IC50	Algae	4.6 mg/L, 72 Hours
Crustacea	EC50	Daphnia	2.1 mg/L, 48 Hours

Components	Species		Test Results
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	7.5 - 11 mg/l, 96 hours
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)			
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
Naphthalene (CAS 91-20-3)			
Algae	IC50	Algae	0.4 mg/L, 72 Hours
Crustacea	EC50	Daphnia	2.16 mg/L, 48 Hours
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1.09 - 3.4 mg/l, 48 hours
Fish	LC50	Pink salmon (Oncorhynchus gorbuscha)	1.11 - 1.68 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Benzene, ethyl-	3.15
Naphthalene	3.3
Nonane	5.46
Stoddard solvent	3.16 - 7.15

Mobility in soil No data available.

Mobility in general Not available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
US RCRA Hazardous Waste U List: Reference	
Naphthalene (CAS 91-20-3)	U165
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport Information

U.S. Department of Transportation (DOT)

Basic shipping requirements:

UN number	NA1993
Proper shipping name	Combustible liquid, n.o.s. (Distillates (petroleum), light hydrotreated)
Hazard class	Combustible Liquid
Packing group	III
Special provisions	IB3, T1, T4, TP1



15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Nonane (CAS 111-84-2) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

Benzene, ethyl- (CAS 100-41-4) Listed.
Naphthalene (CAS 91-20-3) Listed.
Nonane (CAS 111-84-2) Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Benzene, 1,2,4-trimethyl-	95-63-6	1-5
Benzene, ethyl-	100-41-4	0.1-1
Naphthalene	91-20-3	0.1-1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Benzene, ethyl- (CAS 100-41-4)
Naphthalene (CAS 91-20-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Hazardous Substances (Director's): Listed substance

Benzene, 1,2,4-trimethyl- (CAS 95-63-6) Listed.
Benzene, ethyl- (CAS 100-41-4) Listed.
Naphthalene (CAS 91-20-3) Listed.
Nonane (CAS 111-84-2) Listed.
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7) Listed.
Stoddard solvent (CAS 8052-41-3) Listed.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Benzene, ethyl- (CAS 100-41-4) Listed.
Naphthalene (CAS 91-20-3) Listed.

US - Illinois Chemical Safety Act: Listed substance

Benzene, ethyl- (CAS 100-41-4) Listed.
Naphthalene (CAS 91-20-3) Listed.
Nonane (CAS 111-84-2) Listed.

US - Louisiana Spill Reporting: Listed substance

Benzene, ethyl- (CAS 100-41-4)	Listed.
Naphthalene (CAS 91-20-3)	Listed.
Nonane (CAS 111-84-2)	Listed.

US - Minnesota Haz Subs: Listed substance

Benzene, 1,2,4-trimethyl- (CAS 95-63-6)	Listed.
Benzene, ethyl- (CAS 100-41-4)	Listed.
Naphthalene (CAS 91-20-3)	Listed.
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	Listed.
Stoddard solvent (CAS 8052-41-3)	Listed.

US - New Jersey RTK - Substances: Listed substance

Benzene, 1,2,4-trimethyl- (CAS 95-63-6)	Listed.
Benzene, ethyl- (CAS 100-41-4)	Listed.
Naphthalene (CAS 91-20-3)	Listed.
Nonane (CAS 111-84-2)	Listed.
Stoddard solvent (CAS 8052-41-3)	Listed.

US - New York Release Reporting: Hazardous Substances: Listed substance

Benzene, ethyl- (CAS 100-41-4)	Listed.
Naphthalene (CAS 91-20-3)	Listed.

US - Texas Effects Screening Levels: Listed substance

Benzene, 1,2,4-trimethyl- (CAS 95-63-6)	Listed.
Benzene, ethyl- (CAS 100-41-4)	Listed.
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	Listed.
Naphthalene (CAS 91-20-3)	Listed.
Nonane (CAS 111-84-2)	Listed.
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	Listed.
Stoddard solvent (CAS 8052-41-3)	Listed.

US - Washington Chemical of High Concern to Children: Listed substance

Benzene, ethyl- (CAS 100-41-4)	Listed.
--------------------------------	---------

US. Massachusetts RTK - Substance List

Benzene, 1,2,4-trimethyl- (CAS 95-63-6)	Listed.
Benzene, ethyl- (CAS 100-41-4)	Listed.
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	Listed.
Naphthalene (CAS 91-20-3)	Listed.
Nonane (CAS 111-84-2)	Listed.
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	Listed.
Stoddard solvent (CAS 8052-41-3)	Listed.

US. Pennsylvania RTK - Hazardous Substances

Benzene, 1,2,4-trimethyl- (CAS 95-63-6)	Listed.
Benzene, ethyl- (CAS 100-41-4)	Listed.
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	Listed.
Naphthalene (CAS 91-20-3)	Listed.
Nonane (CAS 111-84-2)	Listed.
Paraffin Oils (petroleum), Catalytic Dewaxed Heavy (CAS 64742-70-7)	Listed.
Stoddard solvent (CAS 8052-41-3)	Listed.

US. Rhode Island RTK

Benzene, 1,2,4-trimethyl- (CAS 95-63-6)	Listed.
Benzene, ethyl- (CAS 100-41-4)	Listed.
Naphthalene (CAS 91-20-3)	Listed.


Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	*	2
FLAMMABILITY		2
PHYSICAL HAZARD		0
PERSONAL PROTECTION		X



Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

29-April-2015

Further information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

Other information

This Safety Data Sheet was prepared to comply with the current OSHA Hazard Communication Standard (HCS) adoption of the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Prepared by

Dell Tech Laboratories Ltd. Phone: (519) 858-5021