

# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/24/2018

Reviewed on 10/24/2018

## 1 Identification

- **Product identifier**
- **Trade name:** Navi-Guard Hi Temp Red Grease EP 2
- **Article number:** 11063-2
- **Details of the supplier of the safety data sheet**
- **Manufacturer:**  
Battenfeld Grease & Oil Corporation of New York  
1174 Erie Ave., PO Box 728  
NORTH TONAWANDA, NY 14120-0728  
USA  
info@battenfeld-grease.com
- **Information department:** Technical Department
- **Emergency telephone number:** During normal opening hours: +1 (716) 695 2100

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07

- **Signal word** Warning
- **Hazard statements**  
Causes serious eye irritation.
- **Precautionary statements**  
Wash thoroughly after handling.  
Wear eye protection / face protection.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing.  
If eye irritation persists: Get medical advice/attention.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 2  
Fire = 1  
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = \*2  
Fire = 1  
Reactivity = 0

(Contd. on page 2)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/24/2018

Reviewed on 10/24/2018

Trade name: Navi-Guard Hi Temp Red Grease EP 2

(Contd. of page 1)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

68457-79-4	Zinc Dialkylthiophosphate	0.5-1.5%
------------	---------------------------	----------

### 4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:** Pick up mechanically.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

471-34-1	calcium carbonate, precipitated	45 mg/m <sup>3</sup>
108-31-6	maleic anhydride	0.2 ppm

- **PAC-2:**

471-34-1	calcium carbonate, precipitated	210 mg/m <sup>3</sup>
----------	---------------------------------	-----------------------

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/24/2018

Reviewed on 10/24/2018

**Trade name: Navi-Guard Hi Temp Red Grease EP 2**

(Contd. of page 2)

108-31-6	maleic anhydride	2 ppm
<b>· PAC-3:</b>		
471-34-1	calcium carbonate, precipitated	1,300 mg/m <sup>3</sup>
108-31-6	maleic anhydride	20 ppm

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

<b>64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic (30-60%)</b>	
ACGIH TLV	Long-term value: 5 mg/m <sup>3</sup>
OSHA PEL	Long-term value: 5 mg/m <sup>3</sup>
<b>64742-01-4 Residual oils (petroleum), solvent-refined (10-30%)</b>	
OSHA PEL	Long-term value: 5 mg/m <sup>3</sup>
<b>64742-52-5 Distillates (petroleum), hydrotreated heavy naphthenic (3-7%)</b>	
ACGIH TLV	Short-term value: 10 mg/m <sup>3</sup> Long-term value: 5 mg/m <sup>3</sup>
OSHA PEL	Long-term value: 5 mg/m <sup>3</sup>
<b>471-34-1 calcium carbonate, precipitated (1-5%)</b>	
PEL	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV	TLV withdrawn

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/24/2018

Reviewed on 10/24/2018

**Trade name: Navi-Guard Hi Temp Red Grease EP 2**

(Contd. of page 3)

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:** Semi-Solid

**Color:** Red

· **Odor:** Petroleum-like

· **Odor threshold:** Not determined.

· **pH-value:** Not applicable.

· **Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** 338 °C (640.4 °F)

· **Flash point:** 244 °C (471.2 °F)

· **Flammability (solid, gaseous):** Not determined.

· **Ignition temperature:** >315 °C (>599 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

**Lower:** Not determined.

**Upper:** Not determined.

· **Vapor pressure:** Not applicable.

· **Density at 20 °C (68 °F):** 0.93329 g/cm<sup>3</sup> (7.78831 lbs/gal)

(Contd. on page 5)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/24/2018

Reviewed on 10/24/2018

Trade name: Navi-Guard Hi Temp Red Grease EP 2

(Contd. of page 4)

· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not applicable.
· <b>Evaporation rate</b>	Not applicable.
· <b>Solubility in / Miscibility with Water:</b>	Insoluble.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not applicable.
<b>Kinematic:</b>	Not applicable.
· <b>Solvent content:</b>	
<b>VOC content:</b>	0.00 % 0.0 g/l / 0.00 lb/gl
<b>Solids content:</b>	11.6 %
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

### · Information on toxicological effects

#### · Acute toxicity:

#### · LD/LC50 values that are relevant for classification:

##### ATE (Acute Toxicity Estimate)

Oral	LD50	>7,324-7,528 mg/kg (rat)
Dermal	LD50	>162,272 mg/kg (rabbit)

#### · Primary irritant effect:

- **on the skin:** No irritant effect.

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

#### · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

#### · Carcinogenic categories

#### · IARC (International Agency for Research on Cancer)

9002-88-4	High Density Polyethylene Polymer	3
-----------	-----------------------------------	---

#### · NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 6)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 10/24/2018

Reviewed on 10/24/2018

**Trade name: Navi-Guard Hi Temp Red Grease EP 2**

(Contd. of page 5)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |  |                 |
|--|-----------------|
| · <b>UN-Number</b>   |                 |
| · <b>DOT, ADN, IMDG, IATA</b>  | not regulated   |
| · <b>UN proper shipping name</b>   |                 |
| · <b>DOT, ADN, IMDG, IATA</b>  | not regulated   |
| · <b>Transport hazard class(es)</b>  |                 |
| · <b>DOT, ADN, IMDG, IATA</b>  |                 |
| · <b>Class</b>   | not regulated   |
| · <b>Packing group</b>   |                 |
| · <b>DOT, IMDG, IATA</b>   | not regulated   |
| · <b>Environmental hazards:</b>  |                 |
| · <b>Marine pollutant:</b>   | No              |
| · <b>Special precautions for user</b>  | Not applicable. |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | Not applicable. |

(Contd. on page 7)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/24/2018

Reviewed on 10/24/2018

Trade name: Navi-Guard Hi Temp Red Grease EP 2

(Contd. of page 6)

· UN "Model Regulation": not regulated

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

### · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

### · Section 313 (Specific toxic chemical listings):

68457-79-4	Zinc Dialkylthiophosphate	0.5-1.5%
108-31-6	maleic anhydride	0.1-1%

### · TSCA (Toxic Substances Control Act):

All ingredients are listed.

### · Proposition 65

#### · Chemicals known to cause cancer:

None of the ingredients is listed.

#### · Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

#### · Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

#### · Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

### · Carcinogenic categories

#### · EPA (Environmental Protection Agency)

None of the ingredients is listed.

#### · TLV (Threshold Limit Value established by ACGIH)

108-31-6	maleic anhydride	A4
----------	------------------	----

#### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

#### · Hazard pictograms



GHS07

#### · Signal word Warning

#### · Hazard statements

Causes serious eye irritation.

#### · Precautionary statements

Wash thoroughly after handling.

Wear eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 8)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 10/24/2018

Reviewed on 10/24/2018

**Trade name: Navi-Guard Hi Temp Red Grease EP 2**

(Contd. of page 7)

*If eye irritation persists: Get medical advice/attention.*

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Department issuing SDS:** Technical Department

· **Contact:** Ms. McDaniel

· **Date of preparation / last revision** 10/24/2018 / 24

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

· **\* Data compared to the previous version altered.**